

# **XML**

Introduction to Databases

CompSci 316 Fall 2022



**DUKE**  
COMPUTER SCIENCE

# Announcements (Thurs. Oct 20)

- HW4 (mini-project, group submission) deadline extended to Monday Oct 24 10 pm
- **Midsemester Feedback Survey due by Friday night** (graded as part of communication 2%)
  - Written comments are helpful!
- Gradiance-4 (B+-tree) due next Wednesday Oct 26
- Discussion this week again on project
- HW5 (Index + XML) posted early next week, due Thursday Nov 3 10 pm

# Structured vs. unstructured data

- Relational databases are highly structured
  - All data resides in tables
  - You must define schema before entering any data
  - Every row confirms to the table schema
  - Changing the schema is hard and may break many things
- Texts are highly unstructured
  - Data is free-form
  - There is no pre-defined schema, and it's hard to define any schema
  - Readers need to infer structures and meanings

What's in between these two extremes?

Home

News!

Background

Research

Publications

Projects


Funding

Teaching

Students

Services

# Sudeepa Roy



**Associate Professor**

[Department of Computer Science](#)

[Duke University](#)

308 Research Drive

Campus Box 90129

Durham, NC 27708-0129

**Office:** D325 LSRC Building

**Phone:** (919)-660-6596

**Fax:** (919) 660-6519

## New

- Show results for
- Any Department
  - Amazon Video
  - TV
  - Movies
- Refine by
- Channels
  - Broadway HD
  - Cinemax
  - Comic-Con HQ
  - EchoBoom Sports
  - Fandor
  - HBO
  - IndieFlix Shorts
  - REELZ NOW
  - Sesio
  - STARZ
  - Stringray Karaoke
  - TheSunNetwork
  - See more
  - Amazon Prime
  - See more
  - New Releases
  - Last 30 Days
  - Last 90 Days
  - Purchase Type
  - Purchase
  - Rental
  - Genre
  - Action & Adventure
  - Comedy
  - Documentary
  - Drama
  - Horror
  - Kids & Family
  - Music Videos & Concerts
  - Mystery & Thrillers
  - Romance
  - Science Fiction
  - Special Interests
  - Sports
  - See more
  - Mood
  - Bleak
  - Exciting
  - Feel Good
  - Funny
  - Offbeat
  - Rough
  - Suspenseful
  - Touching
  - See more
  - Theme

Amazon Video - simpsons

Departments - Your Amazon.com Today's Deals Gift Cards & Registry Sell Help

Amazon Video Originals TV Shows Movies Kids Explore

1-16 of 570 results for Amazon Video - "simpsons"

All Videos (569) Included with Prime (97) Channels (136) Rent or Buy (308) Free with Ads (15)

Sort by Relevance


<p>The Simpsons Movie 2007   PG-13</p> <p>After Homer accidentally pollutes the town's water supply, Springfield is encased in a gigantic dome by the EPA and the Simpson family are declared fugitives.</p> <p>Release: Jul 21, 2007 Directed David Silverman by: Genre: Adventure, Animation, Comedy Runtime: 87 minutes</p> <p>Cast: Dan Castellaneta, Julie Kavner, Nancy Cartwright, Yeardley Smith, Hank Azaria, Harry Shearer, Pamela Hayden, Lisa Simpson, Bart Simpson, Homer Simpson</p> <p>Play trailer</p>	<p>The Simpsons Season 1 1989   CC</p> <p>\$299 - \$1499 Buy episodes or Buy season</p> <p>★★★★★ 860</p>
<p>The Simpsons Season 29 2017   CC</p> <p>\$690 - \$3499 Buy episodes or Buy TV Season Pass</p> <p>★★★★★ 3</p>	<p>The Simpsons Movie 2007   PG-13   CC</p> <p>0.00 Watch with HBO on Amazon Channels. \$699 Buy</p> <p>★★★★★ 553</p> <p>Starring: Dan Castellaneta, Julie Kavner, et al. Directed 20TH_CENTURY_FOX by: Runtime: 1 hr 26 mins</p>
<p>The Simpsons Season 5 1993   CC</p> <p>\$299 - \$1999 Buy episodes or Buy season</p> <p>★★★★★ 321</p>	<p>The Simpsons Season 28 2016   CC</p> <p>\$690 - \$2499 Buy episodes or Buy TV Season Pass</p> <p>★★★★★ 27</p>
<p>The Simpsons Season 7 1995   CC</p> <p>\$299 - \$1999 Buy episodes or Buy season</p> <p>★★★★★ 3</p>	<p>The Simpsons Season 26 2014   CC</p> <p>\$690 - \$1999 Buy episodes or Buy season</p> <p>★★★★★ 67</p>
<p>The Simpsons Season 4 1992   CC</p> <p>\$299 - \$1999 Buy episodes or Buy season</p> <p>★★★★★ 384</p>	<p>The Simpsons Season 17 2006   CC</p> <p>\$299 - \$1999 Buy episodes or Buy season</p> <p>★★★★★ 67</p>
<p>The Simpsons Season 6 1994   CC</p> <p>\$299 - \$1999 Buy episodes or Buy season</p> <p>★★★★★ 556</p>	<p>The Simpsons Season 2 1990   CC</p> <p>\$299 - \$1999 Buy episodes or Buy season</p> <p>★★★★★ 440</p>
<p>The Simpsons Season 15 2003   CC</p> <p>\$299 - \$1999 Buy episodes or Buy season</p> <p>★★★★★ 153</p>	<p>The Simpsons Season 3 1991   CC</p> <p>\$199 - \$1999 Buy episodes or Buy season</p> <p>★★★★★ 153</p>

# Semi-structured data

- **Observation: most data have some structure, e.g.:**
  - Book: chapters, sections, titles, paragraphs, references, index, etc.
  - Item for sale: name, picture, price (range), ratings, promotions, etc.

# XML: eXtensible Markup Language

```
<bibliography>
  <book>
    <title>Foundations of Databases</title>
    <author>Abiteboul</author>
    <author>Hull</author>
    <author>Vianu</author>
    <publisher>Addison Wesley</publisher>
    <year>1995</year>
  </book>
  <book>...</book>
</bibliography>
```



- Text-based
- Capture data (content), not presentation
  - Similar but different from HTML
- Data self-describes its structure
  - Names and nesting of tags have meanings!

# Other nice features of XML

- **Portability**: Just like HTML, you can ship XML data across platforms
  - Relational data requires heavy-weight API's
- **Flexibility**: You can represent any information (structured, semi-structured, documents, ... )
  - Relational data is best suited for structured data
- **Extensibility**: Since data describes itself, you can change the schema easily
  - Relational schema is rigid and difficult to change

# XML terminology

- Tag names: `book`, `title`, ...
- Start tags: `<book>`, `<title>`, ...
- End tags: `</book>`, `</title>`, ...
- An **element** is enclosed by a pair of start and end tags: `<book>...</book>`
  - Elements can be nested: `<book>...<title>...</title>...</book>`
  - Empty elements: `<is_textbook></is_textbook>`
    - Can be abbreviated: `<is_textbook/>`
- Elements can also have **attributes**:  
`<book ISBN="..." price="80.00">`
- Many other features

```
<bibliography>
  <book ISBN="ISBN-10" price="80.00">
    <title>Foundations of Databases</title>
    <author>Abiteboul</author>
    <author>Hull</author>
    <author>Vianu</author>
    <publisher>Addison Wesley</publisher>
    <year>1995</year>
  </book>...
</bibliography>
```

☞ Ordering generally matters, except for attributes




# Well-formed XML documents

A **well-formed** XML document

- Follows XML lexical conventions
  - Wrong: `<section>We show that x < 0...</section>`
  - Right: `<section>We show that x &lt; 0...</section>`
    - Other special entities: `>` becomes `&gt;`; and `&` becomes `&amp;`
- Contains a single root element
- Has properly matched tags and properly nested elements (like parentheses matching)
  - Right: `<section>...<subsection>...</subsection>...</section>`
  - Wrong: `<section>...<subsection>...</section>...</subsection>`
  - Think of `{{()}}{[]}]` matching!

# A tree representation



# DTD and Schema (details omitted)

- DTD (Document Type Definitions)
- Specifies Schema and constraints for XML
- Specifies a grammar (e.g. +, ? for one or more, zero or 1 etc.)
- Another option XML schema (.xsd)

```
<?xml version="1.0"?>
<!DOCTYPE bibliography [
  <!ELEMENT bibliography (book+)>
  <!ELEMENT book (title, author*, publisher?, year?, section*)>
  <!ATTLIST book ISBN ID #REQUIRED>
  <!ATTLIST book price CDATA #IMPLIED>
  <!ELEMENT title (#PCDATA)>
  <!ELEMENT author (#PCDATA)>
  <!ELEMENT publisher (#PCDATA)>
  <!ELEMENT year (#PCDATA)>
  <!ELEMENT i (#PCDATA)>
  <!ELEMENT content (#PCDATA|i)*>
  <!ELEMENT section (title, content?, section*)>
]>

<bibliography>
  <book ISBN="ISBN-10" price="80.00">
    <title>Foundations of Databases</title>
    <author>Abiteboul</author>
    <author>Hull</author>
    <author>Vianu</author>
    <publisher>Addison Wesley</publisher>
    <year>1995</year>
    <section>...</section>...
  </book>
</bibliography>
```

# XML versus relational data

## Relational data

- Schema is always **fixed** in advance and difficult to change
- **Simple, flat table structures**
- Ordering of rows and columns is unimportant
- Exchange is problematic
- “Native” support in all serious commercial DBMS

## XML data

- Well-formed XML **does not require predefined, fixed schema**
- **Nested structure; ID/IDREF(S) permit arbitrary graphs**
- Ordering forced by document format; may or may not be important
- Designed for easy exchange
- Often implemented as an “add-on” on top of relations

# Case study

- Design an XML document representing cities, counties, and states
  - For states, record name and capital (city)
  - For counties, record name, area, and location (state)
  - For cities, record name, population, and location (county and state)
- Assume the following:
  - Names of states are unique
  - Names of counties are only unique within a state
  - Names of cities are only unique within a county
  - A city is always located in a single county
  - A county is always located in a single state

# A possible design

Design an XML document representing cities, counties, and states

For states, record name and capital (city)

For counties, record name, area, and location (state)

For cities, record name, population, and location (county and state)

Assume the following:


Names of states are unique

Names of counties are only unique within a state

Names of cities are only unique within a county

A city is always located in a single county

A county is always located in a single state



# XPath and XQuery

# Query languages for XML

- XPath
  - Path expressions with conditions
  - ☞ Building block of other standards (XQuery, XSLT, XLink, XPointer, etc.)
- XQuery
  - XPath + full-fledged SQL-like query language
- Also XSLT (not covered)
- We would cover only simple queries



# Try the queries in this lecture online

- There are many online Xpath/Xquery testers e.g.,
- <http://codebeautify.org/Xpath-Tester> (XPATh)
- <http://videlibri.sourceforge.net/cgi-bin/xidelcgi> (XQUERY)
- Try with this example (or change it for different queries)
- **Caveats**
  - if you see bad characters, you might have to replace them like “” -> " or .
  - Not everything works all the time! Try different websites and config

```
<bibliography>
<book ISBN="ISBN-10" price="70">
<title>Foundations of Databases</title>
<author>Abiteboul</author>
<author>Hull</author>
<author>Vianu</author>
<publisher>Addison Wesley</publisher>
<year>1995</year>
<section>abc</section>
</book>
<book ISBN="ISBN-11" price="20">
<title>DBSTS</title>
<author>Ramakrishnan</author>
<author>Gehrke</author>
<publisher>Addison Wesley</publisher>
<year>1999</year>
<section>abc</section>
</book>
</bibliography>
```

# Basic XPath constructs

- `/` separator between steps in a path
- `name` matches any child element with this tag name
- `*` matches any child element
- `@name` matches the attribute with this name
- `@*` matches any attribute
- `//` matches any descendent element or the current element itself
- `.` matches the current element
- `..` matches the parent element

# XPath

- XPath specifies path expressions that match XML data by navigating down (and occasionally up and across) the tree
- Example
  - Query: `/bibliography/book/author`
    - Like a file system path, except there can be multiple “subdirectories” with the same name
  - Result: all author elements reachable from root via the path `/bibliography/book/author`

```
<bibliography>
  <book ISBN="ISBN-10" price="70">
    <title>Foundations of Databases</title>
    <author>Abiteboul</author>
    <author>Hull</author>
    <author>Vianu</author>
    <publisher>Addison Wesley</publisher>
    <year>1995</year>
    <section>abc</section>
  </book>
  <book ISBN="ISBN-11" price="20">
    <title>DBSTS</title>
    <author>Ramakrishnan</author>
    <author>Gehrke</author>
    <publisher>Addison Wesley</publisher>
    <year>1999</year>
    <section>abc</section>
  </book>
</bibliography>
```

# Simple XPath examples

- All book titles  
`/bibliography/book/title`
- All book ISBN numbers  
`/bibliography/book/@ISBN`
- All title elements, anywhere in the document  
`//title`
- All section titles, anywhere in the document  
`//section/title`
- Authors of bibliographical entries (suppose there are articles, reports, etc. in addition to books)  
`/bibliography/*/author`

```
<bibliography>
<book ISBN="ISBN-10" price="70">
<title>Foundations of Databases</title>
<author>Abiteboul</author>
<author>Hull</author>
<author>Vianu</author>
<publisher>Addison Wesley</publisher>
<year>1995</year>
<section>abc</section>
</book>
<book ISBN="ISBN-11" price="20">
<title>DBSTS</title>
<author>Ramakrishnan</author>
<author>Gehrke</author>
<publisher>Addison Wesley</publisher>
<year>1999</year>
<section>abc</section>
</book>
</bibliography>
```

# Predicates in path expressions

**[condition]** matches the “current” element if *condition* evaluates to true on the current element

- Books with price lower than \$50  
/bibliography/book[@price<50]
  - XPath will automatically convert the price string to a numeric value for comparison

```
<bibliography>
<book ISBN="ISBN-10" price="70">
<title>Foundations of Databases</title>
<author>Abiteboul</author>
<author>Hull</author>
<author>Vianu</author>
<publisher>Addison Wesley</publisher>
<year>1995</year>
<section>abc</section>
</book>
<book ISBN="ISBN-11" price="20">
<title>DBSTS</title>
<author>Ramakrishnan</author>
<author>Gehrke</author>
<publisher>Addison Wesley</publisher>
<year>1999</year>
<section>abc</section>
</book>
</bibliography>
```

# Predicates in path expressions – contd.

- Books with author “Abiteboul”  
`/bibliography/book[author='Abiteboul']`
- Books with a publisher child element  
`/bibliography/book[publisher]`
- Prices of books authored by “Abiteboul”  
`/bibliography/book[author='Abiteboul']/@price`

```
<bibliography>
<book ISBN="ISBN-10" price="70">
<title>Foundations of Databases</title>
<author>Abiteboul</author>
<author>Hull</author>
<author>Vianu</author>
<publisher>Addison Wesley</publisher>
<year>1995</year>
<section>abc</section>
</book>
<book ISBN="ISBN-11" price="20">
<title>DBSTS</title>
<author>Ramakrishnan</author>
<author>Gehrke</author>
<publisher>Addison Wesley</publisher>
<year>1999</year>
<section>abc</section>
</book>
</bibliography>
```

# More complex predicates

Predicates can use **and**, **or**, and **not**

- Books with price between \$40 and \$50

```
/bibliography/book[40<=@price and
@price<=50]
```

- Books authored by “Abiteboul” or those with price no lower than \$50

```
/bibliography/book[author='Abiteboul' or
@price>=50]
```

```
/bibliography/book[author='Abiteboul' or
not(@price<50)]
```

- Any difference between these two queries?

```
<bibliography>
<book ISBN="ISBN-10" price="70">
<title>Foundations of Databases</title>
<author>Abiteboul</author>
<author>Hull</author>
<author>Vianu</author>
<publisher>Addison Wesley</publisher>
<year>1995</year>
<section>abc</section>
</book>
<book ISBN="ISBN-11" price="20">
<title>DBSTS</title>
<author>Ramakrishnan</author>
<author>Gehrke</author>
<publisher>Addison Wesley</publisher>
<year>1999</year>
<section>abc</section>
</book>
</bibliography>
```

# A tricky example

End of lecture  
10/20 Thurs

- Suppose for a moment that price is a child element of book, and there may be multiple prices per book
- Books with some price in range [20, 50]
  - Wrong answer:  
/bibliography/book[price >= 20 and price <= 50]  
(returns true with one price 10 and one 70!)
  - Correct answer:  
/bibliography/book[price[. >= 20 and . <= 50]]



# Announcements (Tues. Oct 25)

- Gradiance-4 (B+-tree) due next Wednesday Oct 26
- Gradiance (XML) to be posted today due Wednesday Nov 2
- HW5 (Index + XML) posted today/tomorrow, due Thursday Nov 3 10 pm
- Discussion this week on Index/XML
- Check out Ed Post on updates based on mid-sem feedback
  - Check out midsemester percentage on sakai

# Predicates involving node-sets

`/bibliography/book[author='Abiteboul']`

- There may be multiple authors, so author in general returns a **node-set** (in XPath terminology)
- The predicate evaluates to true as long as it evaluates **true for at least one node** in the node-set, i.e., at least one author is “Abiteboul”

- Another tricky query

`/bibliography/book[author='Abiteboul' and author!='Abiteboul']`

- Will it return any books?
- (Returns books with at least one “Abiteboul” and one non-Abiteboul as authors!)

# More XPath operators and functions

Frequently used in conditions:

$x + y$ ,  $x - y$ ,  $x * y$ ,  $x \text{ div } y$ ,  $x \text{ mod } y$

`contains(x, y)` true if string  $x$  contains string  $y$

`count(node-set)` counts the number nodes in  $node\text{-}set$

`position()` returns the “context position” (roughly, the position of the current node in the node-set containing it)

`last()` returns the “context size” (roughly, the size of the node-set containing the current node)

`name()` returns the tag name of the current element

Books with fewer than 10 sections

`/bibliography/book[count(section)<10]`

All elements whose tag names contain “section” (e.g., “subsection”)

`//*[contains(name(), 'section')]`

Title of the first section in each book

`/bibliography/book/section[position()=1]/title`

A shorthand: `/bibliography/book/section[1]/title`

Title of the last section in each book

`/bibliography/book/section[position()=last()]/title`

# XQuery

- XPath + full-fledged SQL-like query language
- XQuery expressions can be
  - XPath expressions
  - **FLWOR expressions (next slide)**
  - Quantified expressions
  - Aggregation, sorting, and more...
- An XQuery expression can return a new result XML document

Sample online Xquery tester:

<http://videlibri.sourceforge.net/cgi-bin/xidelcgi>

Use Xquery 3.0, node format = xml, output format = adhoc,  
and compatibility = Standard Xquery in the settings

# A simple XQuery based on XPath

Find all books with price lower than \$50

```
<result>{  
  doc("bib.xml")/bibliography/book[@price<50]  
}</result>
```

- Things outside {}'s are copied to output verbatim
- Things inside {}'s are evaluated and replaced by the results
  - `doc("bib.xml")` specifies the document to query
  - **Omit this in the online tester**
  - The XPath expression returns a sequence of book elements
  - These elements (including all their descendants) are copied to output

# FLWR expressions

- Retrieve the titles of books published before 2000, together with their publisher

```
<result>{  
  for $b in /bibliography/book  
  let $p := $b/publisher  
  where $b/year < 2000  
  return  
    <book>  
      { $b/title }  
      { $p }  
    </book>  
}</result>
```

- **for:** loop
  - \$b ranges over the result sequence, getting one item at a time
- **let:** “assignment”
  - \$p gets the entire result of \$b/publisher (possibly many nodes)
- **where:** filtering by condition
- **return:** result structuring
  - Invoked in the “innermost loop,” i.e., once for each successful binding of all query variables that satisfies where

# An equivalent formulation

- Retrieve the titles of books published before 2000, together with their publisher

```
<result>{  
  for $b in /bibliography/book[year<2000]  
  return  
    <book>  
      { $b/title }  
      { $b/publisher }  
    </book>  
}</result>
```

# Another formulation

- Retrieve the titles of books published before 2000, together with their publisher

```
<result>{
  for $b in /bibliography/book,
    $p in $b/publisher
  where $b/year < 2000
  return
    <book>
      { $b/title }
      { $p }
    </book>
}</result>
```

} Nested loop

- Is this query equivalent to the previous two?
- Yes, if there is one publisher per book
- No, in general
  - Two result book elements will be created for a book with two publishers
  - No result book element will be created for a book with no publishers



# Yet another formulation

- Retrieve the titles of books published before 2000, together with their publisher

```
<result>{  
  let $b := /bibliography/book  
  where $b/year < 2000  
  return  
    <book>  
      { $b/title }  
      { $b/publisher }  
    </book>  
}</result>
```

- Is this query correct?
- No!
- It will produce only one output book element, with all titles clumped together and all publishers clumped together
- All books will be processed (as long as one is published before 2000)

# An explicit join

- Find pairs of books that have common author(s)

```
<result>{  
  for $b1 in doc("bib.xml")//book  
  for $b2 in doc("bib.xml")//book  
  where $b1/author = $b2/author  
    and $b1/title > $b2/title  
  return  
    <pair>  
      {$b1/title}  
      {$b2/title}  
    </pair>  
}</result>
```

← These are string comparisons,  
not identity comparisons!

# More features

- Subqueries
  - `normalize-space(string)` removes leading and trailing spaces from string, and replaces all internal sequences of white spaces with one white space
- Existential (some) and Universal (all)
- Aggregation
- Conditional
  - Use anywhere you'd expect a value, e.g.:
  - `let $foo := if (...) then ... else ...`
  - `return <bar blah="{ if (...) then ... else ... }"/>`

List each publisher and the average prices of all its books

```
<result>{
  for $pub in distinct-
  values(doc("bib.xml")//publisher)
  let $price :=
  avg(doc("bib.xml")//book[publisher=$pub
  ]/@price)
  return
  <publisherpricing>
    <publisher>{$pub}</publisher>
    <avgprice>{$price}</avgprice>
  </publisherpricing>
}</result>
```

Extract book titles and their authors; make title an attribute and rename author to writer

```
<bibliography>{
  for $b in doc("bib.xml")//bibliography/book
  return
  <book title="{normalize-space($b/title)}">{
    for $a in $b/author
    return <writer>{string($a)}</writer>
  }</book>
}</bibliography>
```

Find titles of books in which XML is mentioned in some section

```
<result>{
  for $b in doc("bib.xml")//book
  where (some $section in $b//section
  satisfies
    contains(string($section),
    "XML"))
  return $b/title
}</result>
```

Find titles of books in which XML is mentioned in every section

```
<result>{
  for $b in doc("bib.xml")//book
  where (every $section in $b//section
  satisfies
    contains(string($section),
    "XML"))
  return $b/title
}</result>
```

# XML to Relational Data

# Which one is easier?

- XML to relational?
- Or
- Relational to XML?


# Mapping XML to relational

- Store XML in a column
  - CLOB (Character Large Object) type
  - Not much useful!
- Alternatives?
  - Schema-oblivious mapping:  
well-formed XML → generic relational schema
    - Node/edge-based mapping for graphs
    - Interval-based mapping for trees
    - Path-based mapping for trees (not covered)
  - Schema-aware mapping (not covered):  
valid XML → special relational schema based on DTD



Only this one in  
this class

# Example – Node/Edge Based



- How would you translate it to a relational schema?
  - Element? Attribute? Parent-child relationship?
  - Keys? (Do not see the next slides yet!)

# Node/edge-based: schema

- *Element(eid, tag)*
  - *Attribute(eid, attrName, attrValue)* Key: (eid, attrName)
    - Attribute order does not matter
  - *ElementChild(eid, pos, child)* Keys: (eid, pos), (child)
    - pos specifies the ordering of children
    - child references either *Element(eid)* or *Text(tid)*
  - *Text(tid, value)*
    - tid cannot be the same as any eid
- ☞ Need to “invent” lots of *id*’s
- ☞ Need indexes for efficiency, e.g., *Element(tag)*, *Text(value)*



# Node/edge-based: example

```
<bibliography>
  <book ISBN="ISBN-10" price="80.00">
    <title>Foundations of Databases</title>
    <author>Abiteboul</author>
    <author>Hull</author>
    <author>Vianu</author>
    <publisher>Addison Wesley</publisher>
    <year>1995</year>
  </book>...
</bibliography>
```

## Attribute

<i>eid</i>	<i>attrName</i>	<i>attrValue</i>
e1	ISBN	ISBN-10
e1	price	80

## Text

<i>tid</i>	<i>value</i>
t0	Foundations of Databases
t1	Abiteboul
t2	Hull
t3	Vianu
t4	Addison Wesley
t5	1995

## Element

<i>eid</i>	<i>tag</i>
e0	bibliography
e1	book
e2	title
e3	author
e4	author
e5	author
e6	publisher
e7	year

## ElementChild

<i>eid</i>	<i>pos</i>	<i>child</i>
e0	1	e1
e1	1	e2
e1	2	e3
e1	3	e4
e1	4	e5
e1	5	e6
e1	6	e7
e2	1	t0
e3	1	t1
e4	1	t2
e5	1	t3
e6	1	t4
e7	1	t5

# Node/edge-based: queries

- `//title`

- `SELECT eid FROM Element WHERE tag = 'title';`

- `//section/title`

- `SELECT e2.eid`  
`FROM Element e1, ElementChild c, Element e2`  
`WHERE e1.tag = 'section'`  
`AND e2.tag = 'title'`  
`AND e1.eid = c.eid`  
`AND c.child = e2.eid;`

<i>eid</i>	<i>attrName</i>	<i>attrValue</i>
e1	ISBN	ISBN-10
e1	price	80

Attribute

<i>eid</i>	<i>tag</i>
e0	bibliography
e1	book
e2	title
e3	author
e4	author
e5	author
e6	publisher
e7	year

Element

<i>eid</i>	<i>pos</i>	<i>child</i>
e0	1	e1
e1	1	e2
e1	2	e3
e1	3	e4
e1	4	e5
e1	5	e6
e1	6	e7
e2	1	t0
e3	1	t1
e4	1	t2
e5	1	t3
e6	1	t4
e7	1	t5

ElementChild

## 👉 Path expression becomes joins!

- Number of joins is proportional to the length of the path expression
- `//bibliography/book[author="Abiteboul"]/@price`
  - More complex SQL queries with EXISTS needed
- `//book//title`
  - Needs recursion (not covered yet)

Text

<i>tid</i>	<i>value</i>
t0	Foundations of Databases
t1	Abiteboul
t2	Hull
t3	Vianu
t4	Addison Wesley
t5	1995