

# SQL: Triggers, Views, Indexes

Introduction to Databases

CompSci 316 Spring 2017



**DUKE**  
COMPUTER SCIENCE

# Announcements (Mon., Feb. 13)

- **Homework #2** due Friday 02/17 11:59 pm
  - Q6 and X1 due on Thursday, 02/23 11:59 pm, after the midterm
- You can now submit your homework also on **sakai**
- Permanent office hour locations!
  - **Mon, Tues, Wed, Thurs (7-9 pm):** LSRC D105
  - **Fri (Bill – 4:30-6:30 pm):** LSRC A247

# SQL: Review of Lecture 7

User (uid, name, age, pop)  
Group (gid, name)  
Member (uid, gid)

- SQL queries and semantics
- e.g. Find average popularity of members in groups of size > 100

```
5 SELECT G.name, AVG(pop)
1 FROM User U, Member M, Group G
2 WHERE U.uid = M.uid AND M.gid = G.gid
3 GROUP BY G.name
4 HAVING COUNT(*) > 100
```

- Set (no duplicates) and bag operations (duplicates allowed)
- Subqueries – FROM, WHERE, WITH
- EXISTS, IN, UNION, ALL, ANY
- Ordering – ORDER BY ASC/DESC

# SQL: Review of Lecture 8

User (uid, name, age, pop)  
Group (gid, name)  
Member (uid, gid)

- NULL and three valued logic
- Outerjoins (full-, left-, right-)
- INSERT / DELETE / UPDATE
- Constraints
  - NOT NULL
  - Key
  - Referential integrity (foreign key)
  - General Assertion
  - Tuple- and attribute-based CHECK's
- Today: a new type of constraint enforcement – “Trigger”

# “Active” data

- DBMS may have to take some actions automatically on update/insert/delete
- Examples?

# “Active” data

- **Constraint enforcement:** When an operation violates a constraint, abort the operation or try to “fix” data
  - Example: enforcing referential integrity constraints
  - Generalize to arbitrary constraints?
- **Data monitoring:** When something happens to the data, automatically execute some action
  - Example: When price rises above \$20 per share, sell
  - Example: When enrollment is at the limit and more students try to register, email the instructor

# Triggers

- A **trigger** is an **event-condition-action (ECA)** rule
  - When **event** occurs, test **condition**;
  - if condition is satisfied, execute **action**
- Example:
  - **Event**: some user's popularity is updated
  - **Condition**: the user is a member of "Jessica's Circle," and *pop* drops below 0.5
  - **Action**: kick that user out of Jessica's Circle



# Trigger example

```
CREATE TRIGGER PickyJessica
```

```
AFTER UPDATE OF pop ON User Event
```

```
REFERENCING NEW ROW AS newUser
```

```
FOR EACH ROW
```

```
WHEN (newUser.pop < 0.5) Condition  
AND (newUser.uid IN (SELECT uid  
FROM Member  
WHERE gid = 'jes'))
```

```
DELETE FROM Member  
WHERE uid = newUser.uid AND gid = 'jes'; Action
```



# Trigger options

- Possible events include:
  - **INSERT ON** *table*
  - **DELETE ON** *table*
  - **UPDATE** [**OF** *column*] **ON** *table*
- Granularity—trigger can be activated:
  - **FOR EACH ROW** modified
  - **FOR EACH STATEMENT** that performs modification
- Timing—action can be executed:
  - **AFTER** or **BEFORE** the triggering event
  - **INSTEAD OF** the triggering event on views (more later)

# Transition variables

- **OLD ROW**: the modified row before the triggering event
- **NEW ROW**: the modified row after the triggering event
- **OLD TABLE**: a hypothetical read-only table containing all rows to be modified before the triggering event
- **NEW TABLE**: a hypothetical table containing all modified rows after the triggering event

☞ Not all of them make sense all the time, e.g.

- **AFTER INSERT statement-level triggers**
  - Can use only NEW TABLE
- **BEFORE DELETE row-level triggers**
  - Can use only OLD ROW
- etc.

# Statement-level trigger example

```
CREATE TRIGGER PickyJessica
```

```
AFTER UPDATE OF pop ON User
```

```
REFERENCING NEW TABLE AS newUsers
```

```
FOR EACH STATEMENT
```

```
DELETE FROM Member  
WHERE gid = 'jes'  
AND uid IN (SELECT uid  
            FROM newUsers  
            WHERE pop < 0.5);
```

# BEFORE trigger example

- Never allow age to decrease

```
CREATE TRIGGER NoFountainOfYouth
```

```
BEFORE UPDATE OF age ON User
```

```
REFERENCING OLD ROW AS o,  
NEW ROW AS n
```

```
FOR EACH ROW
```

```
WHEN (n.age < o.age)
```

```
SET n.age = o.age;
```

☞ BEFORE triggers are often used to “condition” data

☞ Another option is to raise an error in the trigger body to abort the transaction that caused the trigger to fire

# Statement- vs. row-level triggers

Why are both needed?

pros/cons?

- **Certain triggers are only possible at statement level**
  - If the number of users inserted by this statement exceeds 100 and their average age is below 13, then ...
- **Simple row-level triggers are easier to implement**
  - Statement-level triggers require significant amount of state to be maintained in OLD TABLE and NEW TABLE
  - However, a row-level trigger gets fired for each row, so complex row-level triggers may be less efficient for statements that modify many rows

# System issues

- **Recursive firing of triggers**
  - Action of one trigger causes another trigger to fire
  - Can get into an infinite loop
    - Some DBMS leave it to programmers/database administrators (e.g., PostgreSQL)
    - Some restrict trigger actions (e.g., Oracle)
    - Many set a maximum level of recursion (e.g., 16 in DB2)
- **Interaction with constraints (tricky to get right!)**
  - When do we check if a triggering event violates constraints?
    - After a BEFORE trigger (so the trigger can fix a potential violation)
    - Before an AFTER trigger
  - AFTER triggers also see the effects of, say, cascaded deletes caused by referential integrity constraint violations

(Based on DB2; other DBMS may differ)

User (uid, name, age, pop)

# Example in class

- If after update of “pop” values, the average pop drops below 0.7, restore old table
- NOTE: difficult to do row by row

# Views

- A **view** is like a “virtual” table
  - Defined by a query, which describes how to compute the view contents on the fly
  - DBMS stores the **view definition query** instead of view contents
  - Can be used in queries just like a regular table



# Creating and dropping views

- Example: members of Jessica's Circle

```
User (uid, name, age, pop)
Group (gid, name)
Member (uid, gid)
```

- Tables used in defining a view are called “base tables”
  - *User* and *Member* above
- To drop a view
  - **DROP VIEW** `JessicaCircle`;

# Using views in queries

- Example: find the average popularity of members in Jessica's Circle
  - `SELECT AVG(pop) FROM JessicaCircle;`
  - To process the query, replace the reference to the view by its definition

# Why use views?

# Modifying views

- Does it even make sense, since views are virtual?
- It does make sense if we want users to really see views as tables
- Goal: modify the base tables such that the modification would appear to have been accomplished on the view

# A simple case

```
CREATE VIEW UserPop AS  
SELECT uid, pop FROM User;
```

```
DELETE FROM UserPop WHERE uid = 123;
```

translates to:

```
DELETE FROM User WHERE uid = 123;
```

# An impossible case

```
CREATE VIEW PopularUser AS  
  SELECT uid, pop FROM User  
  WHERE pop >= 0.8;
```

```
INSERT INTO PopularUser  
  VALUES(987, 0.3);
```

- No matter what we do on *User*, the inserted row will not be in *PopularUser*

# A case with too many possibilities

```
CREATE VIEW AveragePop(pop) AS  
SELECT AVG(pop) FROM User;
```

- Note that you can rename columns in view definition

```
UPDATE AveragePop SET pop = 0.5;
```

- Set everybody's *pop* to 0.5?
- Adjust everybody's *pop* by the same amount?
- Just lower Jessica's *pop*?

# SQL92 updateable views

- More or less just single-table selection queries (**why?**)
  - No join
  - No aggregation
  - No subqueries
  - Other restrictions like “default/ no NOT NULL” values for attributes that are projected out in the view
    - so that they can be extended with valid/NULL values in the base table
- Arguably somewhat restrictive
- Still might get it wrong in some cases
  - See the slide titled “An impossible case”
  - Adding **WITH CHECK OPTION** to the end of the view definition will make DBMS reject such modifications



# INSTEAD OF triggers for views

```
CREATE TRIGGER AdjustAveragePop
```

```
INSTEAD OF UPDATE ON AveragePop
```

```
REFERENCING OLD ROW AS o,  
              NEW ROW AS n
```

```
FOR EACH ROW
```

```
UPDATE User
```

```
SET pop = pop + (n.pop-o.pop);
```

- What does this trigger do?

# Indexes

- An **index** is an auxiliary persistent data structure
  - Search tree (e.g., B<sup>+</sup>-tree), lookup table (e.g., hash table), etc.
  - ☞ More on indexes later in this course!
- An index on  $R.A$  can speed up accesses of the form
  - $R.A = value$
  - $R.A > value$  (sometimes; depending on the index type)
- An index on  $(R.A_1, \dots, R.A_n)$  can speed up
  - $R.A_1 = value_1 \wedge \dots \wedge R.A_n = value_n$
  - $(R.A_1, \dots, R.A_n) > (value_1, \dots, value_n)$  (again depends)
- ☞ Ordering of index columns is important—**is an index on  $(R.A, R.B)$  equivalent to one on  $(R.B, R.A)$ ?**
- ☞ **How about an index on  $R.A$  plus another on  $R.B$ ?**

# Examples of using indexes: 1/2

- `SELECT * FROM User WHERE name = 'Bart';`
- Without an index on *User.name*:
- With an index on *User.name*:

# Examples of using indexes: 2/2

- `SELECT * FROM User, Member  
WHERE User.uid = Member.uid  
AND Member.gid = 'jes';`  
Recall the semantic for SQL evaluation!
- With an index on *Member.gid* or *(gid, uid)*:
- With an index on *User.uid*:
- Without an index:

# Creating and dropping indexes in SQL

**CREATE [UNIQUE] INDEX *indexname* ON *tablename*(*columnname*<sub>1</sub>, ..., *columnname*<sub>*n*</sub>);**

- With UNIQUE, the DBMS will also enforce that  $\{columnname_1, \dots, columnname_n\}$  is a key of *tablename*

**DROP INDEX *indexname*;**

- Typically, the DBMS will automatically create indexes for PRIMARY KEY and UNIQUE constraint declarations

# Choosing indexes to create

More indexes = better performance? problems?

- 👉 Optimal index selection depends on both query and update workload and the size of tables
  - Automatic index selection is now featured in some commercial DBMS

# SQL features covered so far

- Query
- Modification
- Constraints
- Triggers
- Views
- Indexes