

Due on March 6th, 2017

55 points total

General Directions: If you are asked to provide an algorithm, you should clearly define each step of the procedure, establish its correctness, and then analyze its overall running time. There is no need to write pseudo-code; an unambiguous description of your algorithm in plain text will suffice.

All the answers must be typed, preferably using LaTeX. If you are unfamiliar with LaTeX, you are strongly encouraged to learn it. However, answers typed in other text processing software and properly converted to a pdf file will also be accepted. Before submitting the pdf file, please make sure that it can be opened using any standard pdf reader (such as Acrobat Reader) and your entire answer is readable. **Handwritten answers or pdf files that cannot be opened will not be graded and will not receive any credit.**

Finally, please read the detailed collaboration policy given on the course website. You are **not** allowed to discuss homework problems in groups of more than 3 students. **Failure to adhere to these guidelines will be promptly reported to the relevant authority without exception.**

Problem 1 (20 points)

You have been called to mediate in an “algorithmic dispute” between Alice Algorithmix and Bob Bitfiddler! Alice and Bob have been tasked by a courier company to find routes in Durham such that each destination is reached using the shortest route starting at their delivery center. The company wants to save overhead; therefore, they require that the roads traversed in all the routes should be acyclic (call this a shortest path tree). Having learnt minimum spanning tree (MST) algorithms from you, Alice has found an MST on the Durham roadmap (think of roads as edges and intersections/destinations as vertices) and claims that for every graph, there always exists an MST that is also a shortest path tree. On the other hand, Bob claims that it is possible to have an MST and a shortest path tree that are completely edge-disjoint. (Assume all roads are bi-directional, i.e., the graph is undirected. Also, assume that all edge lengths are positive and distinct.)

- (a) (10 points) Is Alice’s claim correct? Give a proof for your answer.
- (b) (10 points) Is Bob’s claim correct? Give a proof for your answer.

Problem 2 (25 points)

Show that the following algorithm for minimum spanning trees is correct: Initialize F to the empty set. In each round of the algorithm, for each connected component S of G w.r.t. F , add the minimum weight edge in the cut $(S, V \setminus S)$ to F . Initially, F is empty so every vertex is in its own connected component. Terminate when there is only one connected component w.r.t. F . You can assume that all edge weights are distinct.

(Hint: First, show that F remains acyclic throughout the algorithm. Then, use the generic property of minimum spanning trees proved in class to show that the algorithm computes a minimum spanning tree.)